## MAINTENANCE-FREE BATTERY VRLA AGM

## **VPRO 26Ah 12V**

VPRO batteries by VOLT Polska are designed with VRLA AGM (Absorbent Glass Mat) technology, high performance plates and electrolyte to give extra power output for common power backup system. The general features are: heavy duty grid, non-spillable construction, mechanized assembly, high reliability and stability, sealed and maintenance-free, long life and low self-discharge design. VPRO batteries have 8-10 years design life at 25°C. They can be applied in emergency power system, communication equipment, alarm system, telecommunication systems, marine equipment, uninterruptible power supplies, medical equipment, fire and security system.

Main technical data:


| IVIAIII LECIIIIICAI UALA. |              |                         |  |  |
|---------------------------|--------------|-------------------------|--|--|
| Nominal voltage           |              | 12 V                    |  |  |
| Rated capcity             |              | 26 Ah                   |  |  |
| Dimension                 | total height | 127 mm                  |  |  |
|                           | height       | 125 mm                  |  |  |
|                           | width        | 175 mm                  |  |  |
|                           | length       | 166 mm                  |  |  |
| Approx Weight             |              | 7.2kg (15.87lbs) +/- 3% |  |  |
| Gross dimensions          |              | 18,5x17,3x14,3cm        |  |  |
| Gross weight              |              | 7,7kg                   |  |  |

Other specification:


|  | 20h (10,5V) | 26 Ah         |
|--|-------------|---------------|
| Capacity                               | 10h (10,8V) | 21,5 Ah       |
| (at 25°C)                              | 5h (10,5V)  | 20,5 Ah       |
|  | 1h (9,6V)   | 14,4 Ah       |
| Internal R                             | ~ 15 mΩ     |               |
| Congoity                               | 40°C        | 102%          |
| Capacity<br>affected<br>by temperature | 25°C        | 100%          |
|  | 0°C         | 85%           |
|  | -15°C       | 65%           |
| Self discharge<br>(at 25°C)            | 3 months    | 91%           |
|  | 6 months    | 82%           |
|  | 12 months   | 64%           |
| Working te                             | 25°C +- 3°C |               |
| Working<br>temperature                 | Discharge   | -15°C to 50°C |
|  | Charge      | -10°C to 50°C |
| temperature                            | Storage     | -20°C to 50°C |
| Float Use (25°C)                       | 13,5 VDC    | 13,8 VDC      |
| Cycle Use (25°C)                       | 14,4 VDC    | 14,7 VDC      |
| Max charg                              | 7,2 A       |               |
| Max discha                             | 360 A (5 s) |               |
| Design li                              | 8-10 years  |               |







Dimension



Ø 12

M5

Terminal type (mm):

